



animeo solo 1 Output to IGC4N1 Master  
CAT-5e or higher TIA-568B standard with RJ-45

animeo solo	Color	Pin #
Down	Green	6
Up	Brown White	7
Common	Brown	8

IGC4n1 Wiring Pinout  
CAT-5e or higher TIA-568B standard with RJ-45

Pin #	Color	Function	Shutter Mode Function
1	Orange White	IP 1	N/A
2	Orange	IP 2	N/A
3	Green White	IP 3	N/A
4	Blue	12V+	12V+ (RTS Receiver Only)
5	Blue White	N/A	N/A
6	Green	Down	Down
7	Brown White	Up	Up
8	Brown	Ground	Ground

- Note:
- Integration is via DCT controls by connecting corresponding wires above from the desired control port to a third party controlled relay.
  - STOP command is triggered by activating the UP and DOWN simultaneously.
  - Both IGC4n1 and ICG4n1 Shutter Mode are compatible with animeo Solo.
  - Both IGC4n1 and ICG4n1 Shutter Mode are compatible with IGC4n1 RTS Receiver.
  - IGC4n1 is compatible with DecoFlex Dry Contact Keypad.
  - IGC4n1 Shutter Mode is compatible with animeo Decora Switch or Smooove Origin IB Control, using functions UP, DOWN & STOP only.
  - Max distance for dry contact connectivity using CAT-5e is 300'.

© 2015 Somfy Systems, Inc. All Rights Reserved. This drawing is the property of Somfy Systems, Inc.. The graphics, information and specific ideas in this document are the exclusive property of Somfy Systems, Inc. and must not be made public, copied, or sold. Others seeking permission to reproduce this document, in whole or in part, must obtain permission from Somfy Systems, Inc. in writing.

Tel: 1-800-64-SOMFY  
Fax: 1-609-495-8165  
www.somfysystems.com



Date: 11/12/20  
Print Size: 11" x 17"  
Scale: NTS  
Sales: N/A  
Drawn by: RV  
Checked by:

Revisions			
Rev	Date	By	Description
-	--/--/--	-	
-	--/--/--	-	
-	--/--/--	-	
-	--/--/--	-	

Dwg Title:  
**IGC4N1 to animeo Solo  
1 Zone with Sensors  
Wire Detail**

Dwg No.:  
**IGC4N1-WIRING-03**

Project name:  
**Technical Library**

Client:  
**Somfy Systems, Inc.**

Address:  
**121 Herrod Boulevard  
Dayton, NJ 08810**